



TRAPLINE™ PRO 2

Ammonium Sulfate-free Water Conditioner | Nonionic Surfactant Drift Reduction Agent | Deposition Aid | Anti-foam

CHS Trapline™ Pro 2 contains nonionic surfactants, water conditioning agents, deposition and drift management aids and defoamer. The unique combination of functioning agents improves the performance of glyphosate, dicamba, 2,4-D and many other herbicides that require or recommend surfactant, water conditioning, deposition and drift management as well as reducing foam in the spray tank.

CHS Trapline Pro 2 has been approved for use with XtendiMax® herbicide and is listed on the xtendimaxapplicationrequirements.com website as a Drift Reducing Adjuvant (DRA). When using CHS Trapline Pro 2 with XtendiMax herbicide and XtendiMax tank mixes, no other adjuvant is required. The deposition properties of CHS Trapline Pro 2 further minimize fine spray droplets. The deposition

properties also help to improve leaf coverage and pesticide performance by increasing retention and adhesion of the droplet, maximizing on-target application and performance.

CHS Trapline Pro 2 does not contain ammonium sulfate or acidify the spray solution but uses a proprietary water conditioning system that is compatible with a wide array of herbicides including those that contain glyphosate, dicamba, 2,4-D and many others. Humidome trials with CHS Trapline Pro 2 have demonstrated minimal or no impact on increased dicamba volatility. Wind tunnel trials with CHS Trapline Pro 2 have demonstrated reduced fine droplet formation from most pesticide spray solutions.

- Complete adjuvant system



Principal Functioning Agents

2-hydroxypropane-1,2,3
carboxylate, complex trihydric
alcohols, oligomeric sugar
alcohol condensat. 34.75%

Constituents ineffective
as spray adjuvants 65.25%
TOTAL 100%

Application Directions

• With XtendiMax

Consult xtendimaxapplicationrequirements.com website for approved tank mix partners.

- Xtendimax herbicide at labeled use rate

- Approved pesticide tank mix partner at labeled use rate
- CHS Trapline Pro 2 at 5 pt/100 gal of water

• With Engenia™

- Engenia herbicide at labeled use rate
- Approved pesticide tank mix partner at labeled use rate
- CHS Trapline Pro 2 recommended at 5 pt/100 gal of water

- CHS Trapline Pro 2 application rate range is 2-8 pt/100 gal of water

• With Glyphosate

- Glyphosate herbicide at labeled use rate
- Conventional tank mix partner at labeled use rate
- CHS Trapline Pro 2 at 4 pt/100 gal of water

Consult pesticide labels for product use rates, instructions and proper mixing order.

Package Size

2x2.5 gal case, 275 gal, Repack, Bulk

Always read and follow label directions.

© 2018 CHS Inc.
CHS Trapline™ Pro 2 is a trademark of CHS Inc.
XtendiMax® is a registered trademark of Monsanto.
Engenia™ is a trademark of BASF.